Chain Grabiq-short Link Grade 10

Product information



General: Chain for lifting. Has a maximum service temperature of 200°C ... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, Code and grade.
Standard: EN 818-2
Warning: Not to be heat treated!

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Chain Grabiq-short Link Grade 10

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Length m	P mm	d mm	w1mm mm	Weight kg
203500600000070	6	1.5	58.9	200	18	6	8.5	0.8
203500700000070	7	1.95	77	200	21	7	10	1.1
203500800000070	8	2.6	102	200	24	8	11	1.4
203501000000070	10	4	158	100	30	10	14	2.3
203501300000070	13	6.8	268	100	39	13	18.8	4
203501600000070	16	10.3	402	100	48	16	21.9	5.6
203502000000070	20	16	630	50	60	20	27	9.4
203502200000070	22	20	785	50	66	22	29	11.9
203502600000070	26	27	1,062	50	78	26	35	16.4
203503200000070	32	40	1,610	25	96	32	41.6	25.8

© November 2026 - All Rights Reserved