

## Tiger winches

---

### Product information



High quality Tiger winch is suitable for both lifting and pulling.

The winch is equipped with an automatic brake function which ensures that there is no risk of load falling or sliding. Brake system and components are encased and protected from dust and rain.

Straps and wire ropes are also available separately as spare parts.

Steel wire rope or strap need to order separately.

Product equipped with wire rope can be used for lifting and pulling and product with strap only for pulling. Check the ropes and traps from technical data tab.

All the dimension data can be found on the documents tab

[... Read more](#)

---

**Material:** Steel

**Marking:** According to standard

**Temperature range:** -40°C - (+)80°C

**Finish:** High quality powder coat, yellow

**Standard:** EN 13157

## Tiger winches

### Technical data

Part code	WLL ton	Gear ratio	Length handle mm	Drum diameter mm	Rope capacity m	Pulling capacity t	Webbing length m	Weight kg
501301850000340	0.185	4,1:1	160	40	36	0.37	9.1	3
501302750000340	0.275	4,1:1	210	50	23	0.55	8.5	3.5
501300410000340	0.41	5:01	320	70	24	0.82	14.1	8
501300060000340	0.6	10:01	320	82	18	1.2	10.6	10.5

### WIRE ROPES WITH LATCH HOOK (for lifting and pulling)

For winch t	Length m	Diameter mm	Breaking strength kg
0,185 / 0,37	30	4	1270
0,275 / 0,55	20	5	2000
0,41 / 0,82	22	6	3000
0,6 / 1,2	16	8	4500

### STRAPS WITH LATCH HOOK (only for pulling)

For winch t	Length m	Diameter mm	Breaking strength kg
0,185 / 0,37	6	48	2068
0,275 / 0,55	6	48	2068
0,41 / 0,82	9	54	2864
0,6 / 1,2	9	60	4136