

Bolt Type Chain Shackle Crosby G-2150



Product information

Design: Bolt Type Chain shackle. Thin hex head bolt/nut with cotter pin.

Meets the performance requirements of Federal Specification RR-C-271H, Type IVB, Grade A, Class 3, except for those provisions required of the contractor.

Material: Forged — Quenched and Tempered, with alloy pins.

Marking: According to standard, CE-marked

Finish: Hot Dip galvanized or self colored.

Standard: EN 13889

Safety factor: 6:1

Grade: 6

| Part code | WLL ton | A mm | B mm | D mm | F mm | G mm | K mm | M mm | P mm | R mm | A Tolerance +/- | G Tolerance +/- | Weight kg |
|--------------|---------|------|------|------|------|------|------|------|------|------|-----------------|-----------------|-----------|
| 420100050040 | 0.5 | 11.9 | 7.9 | 6.4 | 15.5 | 19.1 | 40.4 | 24.6 | 39.6 | 6.35 | 1.5 | 1.5 | 0.06 |
| 420100750040 | 0.75 | 13.5 | 9.7 | 7.9 | 19.1 | 25.4 | 48.5 | 29.5 | 46.2 | 7.85 | 1.5 | 1.5 | 0.1 |
| 420100100040 | 1 | 16.8 | 11.2 | 9.7 | 23.1 | 31 | 58.5 | 35.8 | 55 | 9.65 | 1.5 | 3.3 | 0.15 |
| 420100150040 | 1.5 | 19.1 | 12.7 | 11.2 | 26.9 | 36.1 | 67.5 | 41.4 | 63.5 | 11.2 | 1.5 | 3.3 | 0.22 |
| 420100200040 | 2 | 20.6 | 16 | 12.7 | 30.2 | 41.4 | 77 | 46 | 71 | 12.7 | 1.5 | 3.3 | 0.34 |
| 420100330040 | 3.25 | 26.9 | 19.1 | 16 | 38.1 | 51 | 95.5 | 58.5 | 89.5 | 16 | 1.5 | 3.3 | 0.67 |
| 420100480040 | 4.75 | 31.8 | 22.4 | 19.1 | 46 | 60.5 | 115 | 70 | 103 | 20.6 | 1.5 | 6.35 | 1.14 |
| 420100650040 | 6.5 | 36.6 | 25.4 | 22.4 | 53 | 71.5 | 135 | 81 | 120 | 24.6 | 1.5 | 6.35 | 1.75 |
| 420100850040 | 8.5 | 42.9 | 28.7 | 25.4 | 60.5 | 81 | 151 | 93.5 | 135 | 25.4 | 1.5 | 6.35 | 2.52 |
| 420100950040 | 9.5 | 46 | 31.8 | 28.7 | 68.5 | 91 | 172 | 103 | 150 | 31.8 | 1.5 | 6.35 | 3.45 |
| 420101200040 | 12 | 51.5 | 35.1 | 31.8 | 76 | 100 | 191 | 115 | 165 | 35.1 | 1.5 | 6.35 | 4.9 |
| 420101350040 | 13.5 | 57 | 38.1 | 35.1 | 84 | 111 | 210 | 127 | 183 | 38.1 | 3.3 | 6.35 | 6.24 |
| 420101700040 | 17 | 60.5 | 41.4 | 38.1 | 92 | 122 | 230 | 137 | 196 | 41.1 | 3.3 | 6.35 | 7.72 |
| 420102500040 | 25 | 73 | 51 | 44.5 | 106 | 146 | 279 | 162 | 230 | 54 | 3.3 | 6.35 | 14.2 |
| 420103500040 | 35 | 82.5 | 57 | 51 | 122 | 172 | 312 | 184 | 264 | 60 | 3.3 | 6.35 | 21.2 |
| 420105500040 | 55 | 105 | 70 | 66.5 | 145 | 203 | 377 | 238 | 344 | 66.5 | 6.35 | 6.35 | 38.6 |
| 420108500040 | 85 | 127 | 82.5 | 76 | 165 | 216 | 429 | 279 | 419 | 89 | 6.35 | 6.35 | 56.4 |

Blueprint

