Screw Pin Chain Shackle Crosby G-210

Product information



Design: Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

... *Read more*

Material: Forged - Quenched and Tempered, with alloy pins.
Marking: According to standard, CE-mark
Temperature range: -40° C to 204° C
Finish: Hot Dip galvanized or self colored.
Standard: US. FED. SPEC. RR-C-271F, ASME B30.26

Safety factor: 6:1
Grade: 6

© November 2026 - All Rights Reserved

Screw Pin Chain Shackle Crosby G-210

Blueprint



Technical data

Part code	WLL ton	Size inch	A mm	B mm	C mm	D mm	F mm	G mm	H mm	L mm	M mm	P mm	Weight kg
420100050030	0.5	1/4	12	8	22	6	16	25	40	5	36	6	0.05
420100750030	0.75	5/16	14	10	26	8	19	29	48	6	43	8	0.08
420100100030	1	3/8	17	11	32	10	23	36	59	6	52	10	0.13
420100150030	1.5	7/16	19	13	37	11	27	41	68	8	60	11	0.2
420100200030	2	1/2	21	16	41	13	30	46	77	10	68	13	0.27
420100330030	3.25	5/8	27	19	51	16	38	59	96	11	85	16	0.57
420100480030	4.75	3/4	32	22	60	19	46	70	115	13	101	21	1.03
420100650030	6.5	7/8	37	25	71	22	53	81	135	13	114	25	1.43
420100850030	8.5	1	43	29	81	25	60	94	151	14	130	25	2.15
420100950030	9.5	11/8	46	32	90	29	68	103	172	16	152	32	3.06
420101200030	12	11/4	52	36	100	32	76	115	191	18	165	35	4.11
420101350030	13.5	13/8	57	40	111	35	84	127	210	19	176	38	5.28
420101700030	17	11/2	60	42	124	38	92	137	230	21	189	41	7.23
420102500030	25	13/4	73	52	146	44	106	162	279	25	233	54	12.1
420103500030	35	2	83	58	171	53	127	184	324	29	263	60	19.2
420105500030	55	21/2	105	71	203	67	144	238	377	35	335	67	32.5

© November 2026 - All Rights Reserved