

Screw Pin Chain Shackle Crosby G-210

Product information



Design: Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

... [Read more](#)

Material: Forged - Quenched and Tempered, with alloy pins.

Marking: According to standard, CE-marked

Temperature range: -40° C to 204° C

Finish: Hot Dip galvanized or self colored.


Standard: US. FED. SPEC. RR-C-271F, ASME B30.26

Safety factor: 6:1

Grade: 6

Screw Pin Chain Shackle Crosby G-210

Blueprint



Technical data

| Part code | WLL ton | Size inch | A mm | B mm | C mm | D, mm | F mm | G, mm | H, mm | L mm | Mmm mm | Pmm mm | Weight kg |
|--------------|---------|-----------|------|------|------|-------|------|-------|-------|------|--------|--------|-----------|
| 420100050030 | 0.5 | 1/4 | 12 | 8 | 22 | 6 | 16 | 25 | 40 | 5 | 36 | 6 | 0.05 |
| 420100750030 | 0.75 | 5/16 | 14 | 10 | 26 | 8 | 19 | 29 | 48 | 6 | 43 | 8 | 0.08 |
| 420100100030 | 1 | 3/8 | 17 | 11 | 32 | 10 | 23 | 36 | 59 | 6 | 52 | 10 | 0.13 |
| 420100150030 | 1.5 | 7/16 | 19 | 13 | 37 | 11 | 27 | 41 | 68 | 8 | 60 | 11 | 0.2 |
| 420100200030 | 2 | 1/2 | 21 | 16 | 41 | 13 | 30 | 46 | 77 | 10 | 68 | 13 | 0.27 |
| 420100330030 | 3.25 | 5/8 | 27 | 19 | 51 | 16 | 38 | 59 | 96 | 11 | 85 | 16 | 0.57 |
| 420100480030 | 4.75 | 3/4 | 32 | 22 | 60 | 19 | 46 | 70 | 115 | 13 | 101 | 21 | 1.03 |
| 420100650030 | 6.5 | 7/8 | 37 | 25 | 71 | 22 | 53 | 81 | 135 | 13 | 114 | 25 | 1.43 |
| 420100850030 | 8.5 | 1 | 43 | 29 | 81 | 25 | 60 | 94 | 151 | 14 | 130 | 25 | 2.15 |
| 420100950030 | 9.5 | 1 1/8 | 46 | 32 | 90 | 29 | 68 | 103 | 172 | 16 | 152 | 32 | 3.06 |
| 420101200030 | 12 | 1 1/4 | 52 | 36 | 100 | 32 | 76 | 115 | 191 | 18 | 165 | 35 | 4.11 |
| 420101350030 | 13.5 | 1 3/8 | 57 | 40 | 111 | 35 | 84 | 127 | 210 | 19 | 176 | 38 | 5.28 |
| 420101700030 | 17 | 1 1/2 | 60 | 42 | 124 | 38 | 92 | 137 | 230 | 21 | 189 | 41 | 7.23 |
| 420102500030 | 25 | 1 3/4 | 73 | 52 | 146 | 44 | 106 | 162 | 279 | 25 | 233 | 54 | 12.1 |
| 420103500030 | 35 | 2 | 83 | 58 | 171 | 53 | 127 | 184 | 324 | 29 | 263 | 60 | 19.2 |
| 420105500030 | 55 | 2 1/2 | 105 | 71 | 203 | 67 | 144 | 238 | 377 | 35 | 335 | 67 | 32.5 |