

Shackle Crosby COLD TUFF G-2140CT

Product information

All sizes are individually proof tested to 2.0 times the Working Load Limit.


... [Read more](#)



Material: Alloy Steel
Marking: CE-marked
Finish: Zinc Primer

Shackle Crosby COLD TUFF G-2140CT

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D, mm	E mm	F mm	H, mm	L mm	Nmm mm	Pmm mm	Weight kg
420103001280	30	60.5	41.4	146	38.9	98.6	91.9	254	175	41.1	196	9.43
420104001280	40	73.2	50.8	178	46.7	127	106	313	224	57.2	237	15.4
420105501280	55	82.6	57.2	197	52.8	146	122	347	258	61	264	23.6
420108501280	85	105	69.9	267	68.8	184	148	455	324	79.2	345	43.5
420112001280	120	127	82.6	330	79.2	200	165	546	371	92.2	384	80.7
420115001280	150	133	95.3	372	91.9	229	203	632	432	111	448	120
420117501280	175	140	108	368	102	254	229	652	457	116	517	153
420120001280	200	184	121	397	114	279	267	743	533	152	539	204
420125001280	250	216	127	508	114	330	305	889	622	165	576	272