



Theatrical Shackle, Crosby S-209T

Product information

- Sizes: 3/8" through 3/4"
- Capacities: 1 through 4-3/4 metric tonnes.
- Fatigue Rated.
- Industry leading 6 to 1 design factor.
- Screw pin anchor shackles meet the performance requirement of Federal Specification RR-C-271G, Type IVA, Grade A, Class 2, except for those provisions required of the contractor.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these shackles meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

Material: Forged - Quenched and Tempered, with alloy pins.

Marking: According to standard, WLL

Finish: Flat black baked on powder coat finish

Standard: EN 13889

Safety factor: 6:1

Grade: 6

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	M mm	P mm	Tolerance +/- A mm	Tolerance +/- C mm	Weight kg
420100101080	1	16.8	11.2	36.6	9.65	26.2	23.1	45.2	63	6.35	51.5	9.65	1.5	3.3	0.14
420100151080	1.5	19.1	12.7	42.9	11.2	29.9	26.9	51.5	74	7.85	60.5	11.2	1.5	3.3	0.17
420100201080	2	20.6	16	47.8	12.7	33.3	30.2	58.5	83.5	9.65	68.5	12.7	1.5	3.3	0.33
420100331080	3.25	26.9	19.1	60.5	16	42.9	38.1	74.5	106	11.2	85	17.5	1.5	6.35	0.62
420100481080	4.75	31.8	22.4	71.5	19.1	51	46	89	126	12.7	101	20.6	1.5	6.35	1.07

Blueprint

