



## Dee Shackle BN Green Pin BigMouth® G-4553

### Product information

The Green Pin BigMouth® Dee Shackle BN is ideal for use in situations where a lifting point is out of reach for a standard shackle. The BigMouth® Dee Shackle BN has a wider inside width and a longer inside length enabling you to connect the shackle to non-typical lifting points. Such lifting points are for example often found in the steel sheet pile wall industry. The lifting points on the pile walls are usually set at a depth at which only a Green Pin BigMouth® Dee Shackle BN can be used to complete the job. The Green Pin BigMouth® Dee Shackle BN is fitted with a safety bolt. Long-term durability is assured due to the galvanization of the Green Pin BigMouth® Dee Shackle BN. The shackle conforms to a range of certifications. The Green Pin BigMouth® Dee Shackle BN is suitable for both one-leg and multi-leg systems and is available in a range with a working load limit from 4.6 up to 15.5 ton.

Certification on request: 2.1, 2.2, 3.1, MTCa

**Material:** bow and pin alloy steel, quenched and tempered

**Marking:** CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** hot dipped galvanized

**Safety factor:** 5:1

**Grade:** 8

Part code	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg
420100461090	4.6	19	22	46	19	70	116	169	154	19	1.5
420100861090	8.6	25	28	59	25	83	140	208	190	25	3.13
420101551090	15.5	38	42	88	38	115	178	281	257	19	9.42

# Blueprint

