

Bow Shackle SC Green Pin Super® G-5261

Product information



The Green Pin Super® Bow Shackle SC is a grade 8 bow shackle with screw pin. The screw pin enables quick (dis)assembly which makes the shackle perfect for rigging activities in which assembly and disassembly occur relatively frequently. Handling of the Green Pin Super® Bow Shackle SC is easier due to its smaller size and weight (with an equal working load limit when compared to non-Super products). Furthermore, the long-term durability of the shackle is assured as a result of its galvanization. Wear and tear of the counter components such as wire rope is also minimized because the chamber in the shackle eye hides the screw thread. The Green Pin Super® Bow Shackle SC is available in a range with a working load limit from 3.3 up to 85t.

Certification on request: 2.1, 2.2, 3.1, MTCa, ABS PDA, ABS MA

[... Read more](#)

Material: Alloy steel, quenched and tempered

Marking: CE-marked

Temperature range: -20°C up to +200°C


Finish: Hot dipped galvanized

Safety factor: 5:1

Grade: 8

Bow Shackle SC Green Pin Super® G-5261

Blueprint



Technical data

Part code	WLL ton	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	Weight kg
420100331530	3.3	13.5	16	34	13	22	51	32	90	73	59	0.36
420100501530	5	16	19	40	16	27	64	43	110	89	75	0.63
420100701530	7	19	22	46	19	31	76	51	129	103	89	1.01
420100951530	9.5	22	25	52	22	36	83	58	144	119	102	1.5
420101251530	12.5	25	28	59	25	43	95	68	164	137	118	2.21
420101501530	15	28	32	67	28	47	108	75	186	153	131	3.16
420101801530	18	32	35	73	32	51	115	83	201	170	147	4.31
420102101530	21	35	38	79	35	57	133	92	227	186	162	5.58
420103001530	30	38	42	88	38	60	146	99	249	203	175	7.43
420104001530	40	45	50	104	45	74	178	126	300	243	216	12.5
420105501530	55	57	57	119	57	83	197	138	341	286	252	17.2
420108501530	85	70	70	145	70	105	260	180	437	354	320	37.6