

## Rigging Screw Gunnebo No. 801 Jaw-Jaw

---

### Product information

**Standard:** Working load acc. to U.S. Fed.spec.FF-T-791.b. Supplied with closed body from 2,5-17 T, larger dimensions open body.

... [Read more](#)

---

**Material:** Quenched and tempered alloy steel.

**Temperature range:** -20°C up to +200°C


**Finish:** Hot dip galvanized.

**Safety factor:** 5:1



## Rigging Screw Gunnebo No. 801 Jaw-Jaw

### Blueprint



### Technical data

Part code	WLL ton	Thread mm	Tensioning length	B mm	F mm	G, mm	H, mm	K mm	L mm	Mmm mm	Nmm mm	Weight kg
422100250360	2.5	M20	210	270	13	21	45	20	16	50	455	2.3
422100500360	5	M24	250	340	19	28	56	28	22	65	570	4.6
422100700360	7	1 1/4"	270	370	22	35	70	38	28	85	680	8
422101000360	10	1 1/2"	300	400	25	40	78	45	32	100	790	14
422101300360	13	1 3/4"	360	500	30	45	90	50	39	105	870	24
422101700360	17	2"	450	600	35	45	100	58	45	120	1,030	38
422102720360	27.2	2.1/2"	534	780	-	-	-	75	57	142	1,312	88
422103400360	34	2.3/4"	576	780	-	-	-	90	70	145	1,418	98