

Rigging Screw Gunnebo No. 802 Jaw-Eye

Product information

Supplied as standard jaw-eye. WLL rated similar to U.S. specification FF-T-791.b.
Proof loaded and approved for lifting.

... [Read more](#)



Material: Quenched & Tempered alloy steel

Marking: WLL.

Temperature range: -20°C up to +200°C

Finish: Hot-dip galvanized


Warning: The turnbuckles are not allowed to be adjusted in length under load, when they are used for lifting!

Safety factor: 5:1

Grade: 8

Rigging Screw Gunnebo No. 802 Jaw-Eye

Blueprint



Technical data

Part code	WLL ton	Thread	Tensioning length	B mm	F mm	G, mm	H, mm	K mm	L mm	Mmm mm	Nmm mm	Weight kg
422100250060	2.5	M 20	210	270	13	21	45	20	16	50	455	2.3
422100500060	5	M24	250	340	19	28	56	28	22	65	570	4.6
422100700060	7	1.1/4"	270	370	22	35	70	38	28	85	680	8
422101000060	10	1.1/2"	300	400	25	40	78	45	32	100	790	14
422101300060	13	1.3/4"	360	500	30	45	90	50	39	105	870	24
422101700060	17	2"	450	600	35	45	100	58	45	120	1,030	38