

Rigging screws Jaw-Jaw E-6353

Product information



Turnbuckles are used for rigging or tensioning wires, ropes, rods etc. They are designed for in-line rigging, tensioning or lashing.

Certification on request: 2.1

... [Read more](#)

Material: Drop forged mild steel

Marking: According to standard


Finish: Electro-galvanized

Standard: DIN 1480

Note: Supplied with locking nuts

Rigging screws Jaw-Jaw E-6353

Blueprint



Technical data

Part code	Length mm	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	Weight kg
492127400950	194-274	8	194	274	110	8.5	12	M6	6	14	0.21
492132500950	236-325	10	236	325	125	11	16	M8	8	18	0.38
492134900950	266-349	12	266	349	125	13	20	M10	10	24	0.66
492140600950	316-406	14	316	406	140	16	30	M12	12	28	1.15
492149000950	374-490	16	374	490	170	18	38	M12	12	32	1.45
492157000950	438-570	20	438	570	200	20	42	M16	16	38	2.61
492161100950	466-611	22	466	611	220	22	44	M18	18	40	3.24
492169100950	514-691	24	514	691	255	24	46	M20	20	42	4.35
492170900950	544-709	30	544	709	255	30	50	M24	22	46	6.48