

## Crosby Sling Saver S-237

---

### Product information



- High Performance Sling Connector is designed to connect to slings of all materials.
- Allows easy connection to master links or eye hooks and is ideal for bridles.
- Increased radius of bow gives wider sling bearing surface resulting in an increased area for load distribution, allows better load distribution on internal fibers.
  - Increases synthetic sling efficiency as compared to master links, shackle bows and conventional eye hooks. This allows 100% of the sling's rated Working Load Limit to be achieved.
- All alloy construction
- Each connector has a Product Identification Code (PIC) for material traceability, along with a frame size and the name Crosby forged into it.
- Crosby Sling Saver hardware meets the requirements for minimum stock diameter or thickness, and effective contact width shown in the Recommended Standards Specification for Synthetic Polyester Round Slings by the Web Sling & Tie Down Association. WSTDA-RS1.

... [Read more](#)

---


**Material:** Alloy steel

**Safety factor:** 4:1

**Grade:** 10

## Crosby Sling Saver S-237

### Blueprint



### Technical data

Part code	WLL ton	A mm	B mm	C mm	E mm	G, mm	H, mm	L mm	Nmm mm	Rmm mm	S mm	Wmm mm	Weight kg
402200280340	2.84	22.4	36.1	50.8	80.8	25.4	20.3	107	26.4	74.2	12.2	35.1	0.52
402200570340	5.67	36.1	38.6	69.9	105	31.8	24.9	144	43.4	100	19	44.5	1.34
402200850340	8.51	41.4	40.1	69.9	111	35.1	27.9	165	51.8	113	23.6	47.8	2.15
402201420340	14.18	50.8	59.2	95.3	152	44.5	35.8	202	57.7	140	26.9	57.2	3.9
402201700340	17.01	50.8	55.9	95.3	157	44.5	35.8	199	57.7	137	26.9	60.5	4.19
402202270340	22.68	57.2	73.9	121	184	57.2	45.2	240	62	164	31	78.5	7.1
402203400340	34.02	65	85.3	146	232	58.7	47.2	281	78	196	38.1	80.3	11.8