



Welded Master Link Crosby A-344

Product information

Features:

- Individually Proof Tested to values shown, with certification.
- Proof Tested with 70% inside width special fixtures sized to prevent localized point loading per EN 1677-4
- Large inside width and length to allow additional room for sling hardware and crane hook.
- Engineered Flat for use with S-1325A coupler link.
- 12mm through 32mm have Engineered Flat.

Material: Alloy steel — Quenched & Tempered

Marking: According to standard, Manufacturers name, traceability code.

Standard: EN 1677

Safety factor: 5:1

Grade: 8

Part code	WLL ton	Size	For chain, 1-leg mm	For chain, 2-leg mm	Proof load ton	A mm	B mm	C mm	G mm	Weight kg
401100320160	3.2	13	6-8	6-8	8	13	60	120	6.5	0.36
401100410160	4.1	17	8-10	8	10.2	17	90	160	8.5	0.84
401100670160	6.7	19	10-13	10	16.7	19	90	160	8.5	1.06
401100700160	7	22	10-13	10	17.5	22	145	275	10.5	2.34
401100880160	8.8	22	13-16	13	22	22	100	180	10.5	1.63
401100890160	8.9	25	13-16	13	22.2	25	145	275	13.5	3.04
401101150160	11.5	25	16	16	28.7	25	115	210	13.5	2.41
401101300160	13	28	16	16	32.5	28	145	275	13.5	3.86
401101700161	17	32	19-20	19-20	42.5	32	145	275	16.7	4.82
401102400160	24	36	20-22	20-22	60	36	155	285	-	6.88
401103150160	31.5	40	23-26	23-26	78.7	40	140	270	-	7.31
401103830161	38.3	45	26	26	95.7	45	180	340	-	12.89
401104500161	45	51	32	32	112.5	51	215	390	-	19.12
401106700160	67	55	32	32	167.5	55	203	406	-	25.1
401109000160	90	70	-	-	225	70	250	450	-	42.8
401112500160	125	80	-	-	312.5	80	260	450	-	57

Blueprint

