



## Clevis Foundry Hook Crosby A-1359

### Product information

- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit.
- Hook can be tip loaded at the reduced Working Load Limit, see below.
- Operator must ensure the load is retained properly in the hook.

**Material:** Forged alloy steel — Quenched & Tempered.

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter	WLL ton	WLL Tip of the Hook ton	A mm	C mm	D mm	F mm	G mm	K mm	N mm	AA mm	Weight kg
402300201730	7	2	1	159	111.3	122.4	63.5	28.7	22.4	39.9	88.9	0.98
402300261730	8	2.6	1.3	159	111	122.4	63.5	28.7	22.4	39.9	88.9	0.93
402300401730	10	4	2	197.1	140.7	147.8	76.2	35.1	33	47.8	101.6	1.95
402300681730	13	6.8	3.4	238.3	169.4	178.8	88.9	41.4	38.1	57.2	114.3	3.62
402301031730	16	10.3	5.1	285.8	195.1	207.5	101.6	55.6	44.5	64.3	127	6.44
402301601730	18-20	16	8	366.5	248.7	245.1	127	61	55.9	86.1	152.4	11.2
402302101730	22-23	21	10	412.8	279.9	280.2	139.7	78	69.1	95	165.1	19.9

# Blueprint

