



Eye Foundry Hook Crosby A-1329

Product information

Features:

- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- Hook can be tip loaded at the reduced Working Load Limit. Operator must ensure the load is retained properly in the hook

Material: Forged Alloy steel - Quenched and Tempered.

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

| Part code | Chain diameter mm | WLL ton | WLL Tip of the Hook ton | B, | D, | I mm | K, | L | M mm | N mm | O mm | Weight kg |
|--------------|----------------------|------------|----------------------------|-------|-------|---------|------|------|---------|---------|---------|--------------|
| 402300261170 | 7-8 | 2.6 | 1.3 | 39.6 | 122.4 | 22.4 | 39.9 | 16 | 122.2 | 63.5 | 28.7 | 0.91 |
| 402300401170 | 10 | 4 | 2 | 52.6 | 147.8 | 33 | 47.8 | 20.6 | 139.7 | 76.2 | 35.1 | 1.72 |
| 402300681170 | 13 | 6.8 | 3.4 | 64.3 | 178.8 | 38.1 | 57.2 | 26.2 | 180.6 | 88.9 | 41.4 | 3.27 |
| 402301031170 | 16 | 10.3 | 5.1 | 76.2 | 207.5 | 44.5 | 64.3 | 31.8 | 202.2 | 101.6 | 55.6 | 5.58 |
| 402301601170 | 18-20 | 16 | 8 | 104.9 | 245.1 | 55.9 | 86.1 | 50 | 273.1 | 127 | 61 | 10.4 |
| 402302101170 | 22-23 | 21 | 10 | 121.2 | 280.2 | 69.1 | 95 | 57.9 | 311.2 | 139.7 | 78 | 18.4 |
| 402302711170 | 26 | 27.1 | 13.5 | 135.4 | 302.3 | 71.9 | 99.8 | 65 | 339.6 | 152.4 | 84.1 | 23.5 |
| 402304101170 | 32 | 41 | 20.5 | 167.9 | 336.6 | 88.9 | 110 | 80 | 387.4 | 165.1 | 97.5 | 38.3 |

Blueprint

