

## Eye Hook Crosby S-1316, Type SHUR-LOC

---

### Product information



- 25% stronger than Grade 80
- Individually Proof tested to 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Eye style is designed with "Engineered Flat" to connect to S-1325 chain coupler.
- Suitable for use with Grade 100 and Grade 80 chain.
- The SHUR-LOCK hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926. 1431 (g) (1)(i)(A) and 1926. 1501(g)(4)(iv)(B).
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles [... Read more](#)

---

**Material:** Forged Alloy steel - Quenched and Tempered.


**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

## Eye Hook Crosby S-1316, Type SHUR-LOC

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	A mm	C mm	D mm	E mm	F mm	H mm	J mm	L mm	AA mm	Weight kg
402300150100	6	1.45	19.8	100	20.1	66	17	7.87	16	29.5	38.1	0.39
402300260100	7-8	2.6	27.4	135	27.9	88.9	22.1	9.91	20.6	37.6	51	0.82
402300400100	10	4	33	167	29.7	112	27.9	12.9	23.9	46.5	63.5	1.54
402300680100	13	6.8	41.9	209	42.4	139	32	17	29.5	56.4	76.2	2.72
402301030100	16	10.3	55.9	256	51.8	167	38.1	22.1	38.1	67.3	89	6.83
402301600100	18-20	16	64	274	56.4	197	51.1	22.1	51.6	89.4	-	8.61
402302000100	22	20	72.9	317	62.2	222	57.7	24.9	55.9	97.3	-	12.7
402302710100	26	27.1	80	371	81.5	251	62.5	32	68.1	104	-	22.45