



Eye Sling Hook Crosby L-1327

Product information

Features:

- 25% stronger than Grade 80.
- Eye Sling hooks incorporate two types of strategically placed markings forged into the product which address two (2) QUIC-CHECK® features: Deformation Indicators and Angle Indicators.
- Low profile hook tip.
- Utilizes S-4320 integrated latch which meets the world standard for lifting.
- Heavy duty stamped latch interlocks with the hook tip.
- High cycle, long life spring.
- When secured with the proper cotter pin through the hole in the tip of hook, meets the intent of OSHA Rule 1926.1431(g) and 1926.1501(g) for personnel lifting.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

Material: Forged Alloy Steel - Quenched and Tempered.

Marking: Product Identification Code (PIC) for material traceability.

Safety factor: 4:1

Grade: 10

Part code	WLL ton	For chain Ø mm	C,	D,	G,	J,	K,	M mm	N mm	O mm	Q mm	T mm	AA mm	Weight kg
402300140080	1.45	6	84.8	72.9	18.5	22.9	16	16	9.1	22.6	19.1	22.1	38.1	0.23
402300250080	2.6	7-8	107	99.1	26.2	30	19.1	19.1	12.7	29.2	19.1	29.5	50.8	0.59
402300400080	4	10	127	110	30.2	38.9	30.2	25.4	14.2	35.6	23.9	31.2	63.5	1.04
402300680080	6.8	13	161	144	36.6	45.2	34.8	29.7	18.3	42.4	28.4	47.8	76.2	2.04
402301030080	10.3	16	189	172	47.8	60.5	42.2	36.6	22.4	56.1	33.3	51.6	102	3.81
402301800080	16	18-20	230	189	57.2	58.2	47.8	41.4	28.2	52.8	62	62.7	102	6.8
402302100080	20	22-23	256	211	65.8	63.5	55.6	49.3	32.3	57.7	72.1	66.5	102	9.39
402302710080	27.1	26	326	262	76.2	83.8	68.3	60.5	39.6	76.7	88.9	71.9	127	17.9
402304100080	41	32	462	357	116	108	95.3	81	50.8	76.2	114	98.6	178	47.6

Blueprint

