



Shank Hook SHUR-LOC, Crosby S-1318A

Product information

All SHUR-LOC® hooks have the following features:

- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive lock latch is self-locking when the hook is loaded.
- The SHUR-LOC® hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Fatigue rated to 20,000 cycles at 1-1/2 times the Working Load Limit.

Material: Forged alloy steel, Quenched & Tempered.

Marking: CE-marked

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	J mm	L	AA* mm	Weight kg
402300151670	6	1.45	20.1	55	84	20.1	66	17	159	16	28.7	38.1	0.45
402300261670	7-8	2.6	25.4	61	106	27.9	89	22.1	195	20.6	35.1	51	0.9
402300401670	10	4	29	75	131	29.7	112	27.9	235	23.9	46.5	63.5	1.61
402300701670	13	7	34	85	160	42.4	138	32	288	29.5	53.5	76.2	3.18

Blueprint

