Eye Point 8-292K UNC Thread

Product information

•Rotates through 360° adjustable in the direction of the load.

•Load rated parts are 100% magnaflux crack detected.

•Individual forged parts and cap screw are traceable to Test Certification.

•Bolts are UNC thread.

•Proof tested to 2.5 times the WLL.

•Fatigue rated to 20,000 cycles at 1.5 times the WLL.

•Quick and simple assembly, just a tapped hole is required.

... *Read more*

Material: Manufactured from alloy steel, quenched and tempered.
Marking: According to standard
Standard: EN 1677-1

© October 2026 - All Rights Reserved

Eye Point 8-292K UNC Thread

Blueprint





Technical data

Part code	WLL ton	Thread Inch	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	S mm	W mm	Weight kg
421100030760	0.3	5/16	10	37.85	25.4	8.38	9.4	11.94	25.15	23.37	6.1	40.64	6.35	43.94	1.14
421100040760	0.4	3/8	10	37.85	25.4	8.38	9.4	14.22	25.15	23.37	6.1	40.64	6.35	43.94	1.14
421100080760	0.75	1/2	10	45.47	30.23	9.91	10.92	19.05	33.02	29.46	9.4	46.99	7.87	52.07	0.23
421100150760	1.5	5/8	30	52.32	35.31	13.97	12.95	23.88	35.05	33.53	11.43	55.88	9.4	60.96	0.41
421100230760	2.3	3/4	70	60.45	40.39	16	14.73	28.7	44.2	37.34	15.24	65.02	12.7	70.1	0.64
421100230765	2.3	7/8	150	60.45	40.39	16	14.73	33.27	44.2	37.34	15.24	65.02	12.7	70.1	0.68
421100320760	3.2	1	150	72.39	48.51	19.02	17.78	38.1	52.83	45.47	19.05	77.98	14.22	84.07	1.13
421100450760	4.5	1 1/4	350	90.68	60.45	23.88	22.35	47.75	61.72	56.64	23.11	95.25	16	104.9	2.13
421100700760	7	1 1/2	410	109.73	72.39	28.96	26.67	57.15	75.95	68.83	30.48	114.05	22.1	125.98	3.95
421100900760	9	1 3/4	550	127.51	82.8	34.04	32	66.8	89.15	78.49	38.1	132.08	25.4	147.07	5.76
421101200760	12	2	550	144.78	95	38.1	36.58	76.2	104.65	93.73	44.45	150.11	25.4	167.89	8.89

© October 2026 - All Rights Reserved