

## Lifting Point 8-211 Long bolt

---

### Product information



- Rotates through 360° and pivot 90°
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

[... Read more](#)

---

**Features:** Built-in RFID/NFC chip

**Material:** Alloy steel, quenched and tempered

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

## Lifting Point 8-211 Long bolt

### Blueprint



### Technical data

Part code	WLL ton	Thread mm	Torque Nm	Pitch DIN13	A mm	B mm	C mm	D, mm	F mm	G, mm	SWmm mm	J mm	K mm	L mm	Nmm mm	E mm	Mmm mm	Weight kg
42158211003105L	0.3	M 8	30	1.25	30	35	35	11	86	55	13	77	34	41	24	76	M 8	0.4
42158211006125L	0.63	M 10	60	1.5	30	35	36	11	86	55	17	78	34	40	24	96	M 10	0.4
42158211010150L	1	M 12	100	1.75	33	38	44	14	99	57	19	89	38	42	31	114	M 12	0.5
42158211015185L	1.5	M 16	150	2	33	38	46	14	99	57	24	89	38	40	31	149	M 16	0.7
42158211025230L	2.5	M 20	250	2.5	50	54	56	16	142	82	30	132	53	70	49	186	M 20	1.7
42158211040265L	4	M 24	400	3	50	54	59	16	143	82	36	132	53	67	45	221	M 24	2
42158211050340L	5	M 30	500	3.5	60	65	81	23	170	99	46	153	64	67	59	278	M 30	2.9
42158211080300L	8	M 36	800	4	77	85	101	27	225	124	55	205	80	97	69	222	M 36	6.9
42158211100350L	10	M 42	1,000	4.5	77	85	104	27	225	124	65	204	79	94	69	272	M 42	7.9
42158211150350L	15	M 42	1,500	4.5	95	104	112	36	258	158	65	229	98	110	98	264	M 42	13.5
42158211200385L	20	M 48	2,000	5	95	104	120	36	260	158	75	230	99	104	98	295	M 48	15.5