# Clevis Foundry Hook X-046 Grade 10

## Product information



At least 25% greater WLL than traditional Grade 8 products.
Testing according to DIN PAS 1061 and ASTM A952/A 952M.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Designed for the assembly of chain slings where wide throat openings are necessary.

... *Read more*


**Material:** Quenched and tempered alloy steel.
**Marking:** According to standard, Size, grade, manufacturer ID, traceability.
**Temperature range:** -40ºC up to +200°C (without reduction in WLL).
**Finish:** Blue painted.
**Standard:** EN 1677-1
**Warning:** Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

**Safety factor:** 4:1
**Grade:** 10

© November 2026 - All Rights Reserved

# Clevis Foundry Hook X-046 Grade 10

## Blueprint




## Technical data

| Part code | Chain diameter mm | WLL ton | EWL mm | A mm | H mm | K mm | P mm | T mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|
| 402300250770 | 7-8 | 2.5 | 133 | 9 | 27 | 133 | 62 | 19 | 0.95 |
| 402300400770 | 10 | 4 | 163 | 11 | 32 | 163 | 74 | 23 | 1.8 |
| 402300670770 | 13 | 6.7 | 200 | 14 | 39 | 200 | 88 | 32 | 3.6 |
| 402301000770 | 16 | 10 | 239 | 18 | 47 | 239 | 98 | 41 | 6.4 |
| 402301600770 | 20 | 16 | 305 | 21 | 62 | 305 | 113 | 46 | 11.2 |

© November 2026 - All Rights Reserved