

## Clevis Grip Safe Locking Hook X-951

---

### Product information



Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL  
... [Read more](#)

---

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C


**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

## Clevis Grip Safe Locking Hook X-951

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	H, mm	K mm	Omm mm	Pmm mm	T mm	Wmm mm	Weight kg
402300400840	10	4	153	12.1	31	153	49	71	27	137	1.9
402300670840	13	6.7	206	15.5	39	203	64	80	34	174	4.1
402301000840	16	10	243	19.1	47	244	78	114	39	212	7.1
402301600840	20	16	310	24	55	312	92	127	54	251	12.7
402301900840	22	20	300	24.2	59	304	98	151	56	258	14.1