

Eye Sling Hook 8-044/S, Yoke

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Powder coating


Standard: EN 1677-2

Safety factor: 4:1

Grade: 8

Eye Sling Hook 8-044/S, Yoke

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	D, mm	H, mm	K mm	P1 mm mm	T mm	Weight kg
401300120900	6	1.12	20	9	20	80	23	16	0.3
401300200900	7-8	2	25	11	23	98	28	20	0.5
401300320900	10	3.15	32	14	31	121	36	23	1
401300530900	13	5.3	40	18	38	152	40	28	1.7
401300800900	16	8	50	22	47	184	44	32	3.2
401301250900	18-20	12.5	60	26	48	218	45	43	5.5
401301500900	22	15	50	31	62	244	73	50	9
401302120900	26	21.2	64	35	80	279	77	60	13.5
401303150900	32	31.5	88	40	86	352	114	65	20