

Swivel Self Locking Hook X-027

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3


Warning: This hook is a positioning device and is not intended to rotate under load.

Safety factor: 4:1

Grade: 10

Swivel Self Locking Hook X-027

Blueprint



Technical data

| Part code | Chain diameter mm | WLL ton | EWL mm | A mm | B mm | D, mm | H, mm | K mm | Pmm mm | T mm | Weight kg |
|--------------|-------------------|---------|--------|------|------|-------|-------|------|--------|------|-----------|
| 420500140940 | 6 | 1.4 | 149 | 32 | 25 | 12 | 19 | 149 | 28 | 15 | 0.7 |
| 420500250940 | 7-8 | 2.5 | 186 | 36 | 30 | 13 | 24 | 186 | 34 | 20 | 1.2 |
| 420500400940 | 10 | 4 | 218 | 41 | 38 | 16 | 30 | 218 | 44 | 26 | 2 |
| 420500670940 | 13 | 6.7 | 276 | 46 | 48 | 21 | 39 | 276 | 51 | 30 | 4.1 |
| 420501000940 | 16 | 10 | 329 | 61 | 56 | 23 | 49 | 329 | 60 | 36 | 7.2 |
| 420501600940 | 20 | 16 | 387 | 74 | 86 | 25 | 65 | 403 | 70 | 53 | 13 |
| 420501900940 | 22 | 19 | 457 | 97 | 98 | 33 | 63 | 454 | 80 | 49 | 20 |
| 420502650940 | 26 | 26.5 | 535 | 123 | 120 | 51 | 69 | 535 | 99 | 56 | 33 |