

Wear Protection Extreema® EP-C

Product information

According to EN-1492 regulations for the safe use of round slings, the sling should always be protected at the attachment point (shackle, pin, axle, etc.) as well as at the hoist (crane hook).

The main application for EP series is to protect the hoist and the object to be lifted for a safer lifting operation.

With Extreema® protection, round slings and lifting slings have a much longer service life and make your working conditions much safer.

The EP-C protector is made from 100% Cordura®. It can be supplied with or without velcro and in various dimensions. It is easy to put on and take off and is the perfect solution for protecting your sling.

The EP-C protection is extremely strong and stretchable. It has proven itself in many industries and for many different applications. The protection prevents damage to the payload; it is resistant to chemicals and extremely resistant to cuts, abrasion and punctures. This makes it perfect for repeated loading of payloads with extremely sharp edges.

Features of Extreema® EP-C protection:

- High durability
- Low elongation
- High flexibility
- High protection against abrasion, tears and heat
- Easy to put on and take off with Velcro fastener

Material: Cordura

Marking: Dyneema



Part code	Length m	Width mm
8005EPC050	0.5	100
8005EPC150	0.5	120
8005EPC250	0.5	150
8005EPC350	0.5	150
8005EPC550	0.5	250

8005EPC950	0.5	450
8005EPC450	0.5	200
8005EPC650	0.5	300
8005EPC750	0.5	350
8005EPC850	0.5	400
8005EPC10050	0.5	500
8005EPC1150	0.5	550
8005EPC1250	0.5	600
8005EPC1350	0.5	700
8005EPC1450	0.5	800
8005EPC1550	0.5	900
8005EPC1650	0.5	1,000
8005EPC1050	0.5	500
8005EPC570	0.7	250
8005EPC1100	1	120
8005EPC2100	1	150
8005EPC0100	1	100
8005EPC3100	1	150
8005EPC4100	1	200
8005EPC5100	1	250
8005EPC6100	1	300
8005EPC7100	1	350
8005EPC8100	1	400
8005EPC9100	1	450
8005EPC10100	1	500
8005EPC11100	1	550
8005EPC12100	1	600

8005EPC12100	1	800
8005EPC13100	1	700
8005EPC14100	1	800
8005EPC15100	1	900
8005EPC16100	1	1,000
8005EPC14150	1.5	800
8005EPC10200	2	500
8005EPC12200	2	600
8005EPC13200	2	700
8005EPC5200	2	250
8005EPC6200	2	300
8005EPC7200	2	350
8005EPC4300	3	200
8005EPC5300	3	250
8005EPC8930	9.3	400