



Inferno® Soft Sling

Product information

Inferno®: The Heat Resistant Soft Sling

The ultra-heat resistant Inferno® soft sling makes it possible to lift heavy payloads when working under extreme heat conditions. Even when the temperature rises to 200°C, the Inferno® soft sling will maintain strength!

Properties:

The Inferno® soft sling is made of 100% Aramid and available from 0,5m to 20m, with a WLL up to 50t. The Inferno® has a vibrant yellow color and can be manufactured in the black color for WLL up to a maximum of 10 tons.

Features:

- Maintains its strength up to 200°C(!)
- Easy to position
- Low D:d ratio
- Soft, lightweight, and easy to handle
- Improves workflow
- High abrasion resistance
- Environmentally friendly due to the long lifespan
- Creates safer lifting conditions

Sustainability:

The Inferno® heat-resistant soft sling jacket is repairable, making it a sustainable option. In case of damage to the jacket, it can be repaired, extending the lifespan of the sling and reducing waste.

Material: 100% Aramid

Marking: According to standard, CE-marked, UKCA-marked

Temperature range: Up to +200°C

Standard: EN 1492-2

except material

Note: kg/m = kg/EWL

Warning: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Part code

WLL
ton

EWL
m

Colour

340500100100110	1	1	Black
340500100150110	1	1.5	Black
340500100200110	1	2	Black
340500200050110	2	0.5	Black
340500200100110	2	1	Black
340500200200110	2	2	Black
340500200300110	2	3	Black
340500200400110	2	4	Black
340500200500110	2	5	Black
340500300050110	3	0.5	Yellow
340500300100110	3	1	Yellow
340500300200110	3	2	Yellow
340500300300110	3	3	Yellow
340500300400110	3	4	Yellow
340500300500110	3	5	Yellow
340500500050110	5	0.5	Yellow
340500500100110	5	1	Yellow
340500500200110	5	2	Yellow
340500500300110	5	3	Yellow
340500500400110	5	4	Yellow
340500500500110	5	5	Yellow
340501000050110	10	0.5	Yellow
340501000100110	10	1	Yellow
340501000200110	10	2	Yellow
340501000300110	10	3	Yellow
340501000400110	10	4	Yellow

