

Wear Protection Sleeve Secutex

Product information

General: Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Design: Single- or double side polyuretan coated polyester tube or double side polyurethane coated clip.


Max working temp: apx -30° - +70°C, short expose to apx +90°C.

Material: Polyester with 5 mm polyurethane coating. Resistant to most acids but not strong alkalizes.

Part code	Code	Width mm	Height mm	Fit Webwidth mm	Fit Roundsling ton	Weight kg/m
8025SF1030	SF1-30	55	30	-	-	0.8
8025SF1050	SF1-50	70	23	50	1	0.9
8025SF1060	SF1-060	85	23	-	-	1
8025SF1065	SF1-65	80	23	60	2	1.1
8025SF1060	SF1-60	85	23	-	-	1.2
8025SF1075	SF1-75	95	25	75	3	1.3
8025SF1100	SF1-100	125	25	90	4	1.5
8025SF1090	SF1-90	115	25	-	-	1.5
8025SF1125	SF1-125	145	25	120	5-6	1.9
8025SF1120	SF1-120	145	25	-	-	2
8025SF1150	SF1-150	175	25	240	8	2.1
8025SF1180	SF1-180	210	30	-	-	2.9
8025SF1300	SF1-300	330	28	300	≥10	3.7
8025SF1240	SF1-240	85	35	-	-	3.7
8025SF2240	SF2-400	270	35	-	-	5.5
8025SF2300	SF2-300	340	35	-	-	6.8
8025SF1A180	SF1A-180	-	-	-	-	-

Technical data

Protecting sleeves SF-2/double side

**Code****Fit****Width****Height****Weight****Art No****Web width****Round sling****mm****tons****mm****mm****kg/m**

05.30SF2.050

SF-2.50

50

1

70

25

1,2

05.30SF2.065

SF-2.65

60

2

80

25

1,5

12.40SF2.075

SF-2.75

75

3

95

25

1,8

05.30SF2.100

SF-2.100

90

4

125

25

2,1

05.30SF2.125

SF-2.125

120

5-6

145

25

2,6

12.40SF2.150

SF-2.150

240

8

175

25

3,0

12.40SF2.300

SF-2.300

300

≥10

330

30

6,5

Clamp sleeves SC/double side**Code****Fit****Width****Height****Weight****Web width****Round sling****mm****tons****mm****mm****kg/m**

12.40SC.050

SC.50

50

1

70

25

1,1

05.30SC.065

SC.65

65

2

80

25

1,3

05.30SC.075

SC.75

75

3

95

25

1,6

05.30SC.100

SC.100

100

4

125

25

1,8

05.30SC.125

SC.125

125

5

145

25

2,3

12.40SC.150

SC.150

150

8

175

25

2,6

12.40SC.300

SC.300

300

≥10

330

30

6,3

