



Beam Clamp IPSTARTEC11

Product information

IPSTARTEC11 lifting clamps are suitable for horizontal (with flanges horizontal) lifting, transport, stacking and controlled tilting of steel IPE-en HEA-profiles. By placing the chain guide in the appropriate position, it is easy to switch from lifting to tilting and back again, which shifts the center of gravity.

Features:

- Available in capacities of 1.5 and 2.5 metric tons.
- Jaw openings available: 6 to 20mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Features:

Material: Alloy steel.

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

Temperature range: -40°C up to +100°C

Standard: EN 13155

| Part code | WLL ton | Jaw width mm | Model | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | K mm | Weight kg |
|-----------------|---------|--------------|-----------------|------|------|------|------|------|------|------|------|------|------|-----------|
| 502100150120240 | 1.5 | 6-12 | 1.5-IPSTARTEC11 | 6-12 | 140 | 39 | 575 | 110 | 81 | 129 | 126 | 54 | 16 | 6.6 |
| 502100250200240 | 2.5 | 6-20 | 2.5-IPSTARTEC11 | 6-20 | 210 | 55 | 725 | 135 | 115 | 182 | 140 | 74 | 18 | 14.5 |

Blueprint

