

## Horizontal Lifting Clamp IPH10E/IPH10JE

---

### Product information



For horizontal lifting and transfer.

#### Features:

- Available in capacities of 2.0 thru 12 metric tons.
- Wide variety of jaw openings available: 0 to 120mm.
- Equipped with handle for easy placement.
- Individually Proof Tested to 2 times the Working Load Limit with certification [... Read more](#)

---

**Material:** Alloy steel


**Marking:** According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

**Temperature range:** -40°C up to +100°C

**Standard:** EN 13155

## Horizontal Lifting Clamp IPH10E/IPH10JE

### Blueprint



### Technical data

Part code	Code	WLL ton	Jaw width mm	B mm	C mm	E mm	F mm	G, mm	H, mm	J mm	K mm	L mm	Weight kg
502100200601510	IPH10E	2	0-60	117	16	22	109	256	110	20	40	9	5.5
502100300601510	IPH10E	3	0-60	117	20	26	109	266	120	20	48	11	7.5
502100450601510	IPH10E	4.5	0-60	132	25	30	104	280	130	20	48	12	10.5
502100600601510	IPH10E	6	0-60	143	25	36	123	320	130	20	48	14	13
502100900601510	IPH10E	9	0-60	157	30	43	133	330	140	25	62	16	18.5
502101200601510	IPH10E	12	0-60	172	30	47	141	353	150	25	62	17	21.5