

Snatch Block Green Pin® type 601S P-6951

Product information



The Green Pin® Snatch Block S is a light-weight snatch block type 601S with a Green Pin® Shackle attached. The Green Pin® Snatch Block S has a smooth, uninterrupted pull due to conical roller bearings. Its coating ensures long-term durability, even under harsh conditions. The Green Pin® Snatch Block S is available in a range with a working load limit from 2 up to 125 ton in several sheave diameters for steel wire rope diam 7 up to 76 mm.

Certification on request: 2.1, 2.2, MTCb

[... Read more](#)

Material: Carbon steel, fitted with conical roller bearings

Marking: According to standard, CE-marked

Finish: Painted


Standard: EN 13157

Note: WLL is on the headfitting

Safety factor: 4:1

Snatch Block Green Pin® type 601S P-6951

Blueprint



Technical data

Part code	Rope Ø range mm	WLL ton	Sheave dia mm	a mm	b mm mm	c mm	dmm mm	e mm mm	Weight kg
4241BKOFFSS0302	7-9	2	75	75	291	43	82	87	3.87
4241BKOFFSS0404	10-12	4	115	115	363	58	120	89	6.36
4241BKOFFSS0804	10-12	4	200	200	478	58	210	119	11.7
4241BKOFFSS0604	12-14	4	150	150	417	58	160	89	8.64
4241BKOFFSS060816	14-16	8	150	150	478	68	160	119	14.9
4241BKOFFSS100816	14-16	8	250	250	581	68	260	104	26
4241BKOFFSS0608	20-22	8	150	150	478	68	160	119	14.1
4241BKOFFSS0808	20-22	8	200	200	527	68	210	119	19.4
4241BKOFFSS1008	20-22	8	250	250	581	68	260	104	24.7
4241BKOFFSS1208	20-22	8	300	300	646	68	310	106	32
4241BKOFFSS1608	20-22	8	400	400	756	68	415	119	35
4241BKOFFSS1408	20-22	8	350	350	691	68	360	119	40
4241BKOFFSS1808	20-22	8	450	450	817	68	465	119	57.5
4241BKOFFSS061216	14-16	12	150	150	551	83	160	119	20.4
4241BKOFFSS081216	14-16	12	200	200	580	83	210	125	28.5
4241BKOFFSS0612	20-22	12	150	150	551	83	160	119	20
4241BKOFFSS0812	20-22	12	200	200	580	83	210	125	28.2
4241BKOFFSS1012	20-22	12	250	250	679	83	260	125	34.5
4241BKOFFSS1212	20-22	12	300	300	748	83	310	146	49.5
4241BKOFFSS1412	20-22	12	350	350	773	83	360	145	58
4241BKOFFSS1612	20-22	12	400	400	822	83	410	170	67.5
4241BKOFFSS1812	20-22	12	450	450	877	83	465	170	82

Snatch Block Green Pin® type 601S P-6951

Technical data

Part code	Rope Ø range mm	WLL ton	Sheave dia mm	a mm	b mm mm	c mm	dmm mm	e mm mm	Weight kg
4241BKOFFSS0615	24-26	15	150	150	585	92	160	138	24.8
4241BKOFFSS0815	24-26	15	200	200	646	92	210	142	30
4241BKOFFSS1015	24-26	15	250	250	705	92	260	146	43.5
4241BKOFFSS1215	24-26	15	300	300	771	92	310	142	51.5
4241BKOFFSS1415	24-26	15	350	350	798	92	365	171	63
4241BKOFFSS1615	24-26	15	400	400	848	92	415	170	69.5
4241BKOFFSS1815	24-26	15	450	450	898	92	465	170	83
4241BKOFFSS1422	28-32	22	350	350	950	126	365	180	94
4241BKOFFSS1622	28-32	22	405	405	1,007	126	415	180	110
4241BKOFFSS1822	28-32	22	450	450	1,057	126	465	180	124
4241BKOFFSS1830	28-32	30	450	450	1,101	138	465	210	218
4241BKOFFSS1630	32-38	30	405	405	1,076	138	415	210	139
4241BKOFFSS2332	28-32	32	280	594	1,250	138	610	193	280
4241BKOFFSS1632	28-35	32	188	415	1,060	138	428	193	188
4241BKOFFSS1832	28-38	32	210	467	1,111	138	480	193	210
4241BKOFFSS2032	28-38	32	240	505	1,152	138	520	193	240
4241BKOFFSS2036	28-38	36	250	505	1,201	160	520	203	250
4241BKOFFSS2354	38-51	54	468	623	1,540	180	638	269	468
4241BKOFFSS2375	44-51	75	637	623	1,815	190	638	266	637
4241BKOFFSS3075	44-57	75	780	749	1,955	190	770	266	780
4241BKOFFSS32100	64-67	100	1,186	845	2,314	238	860	260	1,186
4241BKOFFSS35125	70-76	125	1,363	950	2,514	275	965	260	1,363