

## Connecting Link Green Pin® MJ

---

### Product information



The Green Pin® Connecting Link EN1677-1 is a grade 8 connecting link according to European standard for components for sling EN 1677-1. These connectors provide fast, easy assembly by using just a hammer. It is designed to connect eye and eye swivel hooks and master links to grade 8 chains all together. The spring bush ensures that the pin stays secured in place within the two halves of the connecting link. The Green Pin® Connecting Link EN1677-1 is available in a range to suit 6 mm up to 32 mm grade 8 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

[... Read more](#)

---

**Material:** alloy steel

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Finish:** painted white


**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 8

## Connecting Link Green Pin® MJ

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	Weight kg
401200110430	6	1.12	8	42	11	20	52	11	15	0.09
401200200430	7-8	2	9	53	14	20	55	13	19	0.15
401200320430	10	3.2	10	66	18	23	64	18	23	0.28
401200540430	13	5.4	14	83	21	32	85	24	28	0.64
401200820430	16	8.2	17	103	25	40	105	28	34	1.16
401201280430	18-20	12.8	21	120	33	50	129	33	42	1.95
401201550430	22	15.5	23	143	40	55	140	37	51	2.94
401202160430	26	21.6	26	169	45	60	153	46	57	4.12
401203280430	32	32.8	39	197	52	68	174	56	67	8.3