

Clevis Self Locking Hook Green Pin® UXLC

Product information



The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The clevis design enables a direct connection to grade 10 chain. The Green Pin® Self-Locking Hook CL is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb

[... Read more](#)

Material: Alloy steel, quenched and tempered

Temperature range: -40°C up to +200°C

Finish: Painted blue

Safety factor: 4:1

Grade: 10

Clevis Self Locking Hook Green Pin® UXLC

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg
402300140690	6	1.4	92	7	32	16	26	28	77	131	8	0.49
402300260690	8	2.6	116	9	43	23	29	32	92	161	10	0.91
402300400690	10	4	143	12	47	32	35	42	111	200	13	1.77
402300680690	13	6.8	167	15	61	37	45	54	142	242	16	3.33
402301030690	16	10.3	201	19	74	43	54	68	185	293	20	6.75
402301600690	20	16	234	23	90	52	61	82	205	339	24	9.57