

Excavator Hook Green Pin® GH

Product information



These excavator hooks are welded directly to the booms of bucket or crane loaders. (Welding instructions are supplied with each hook). These hooks can also be welded on a beam to create a lifting beam. The large surface with chamfer makes the welding easy and safe. Latches are fitted as standard, to prevent accidental unhooking.

Excavator Hooks is available in a range with a working load limit from 1 t. up to 15 t.

Certification on request: 2.1, 2.2, MTCa, MPIb

[... Read more](#)

Material: Alloy steel, quenched and tempered

Temperature range: -40°C up to +200°C

Finish: Painted white


Note: Lifting with the teeth of an excavator is not allowed. Welding must be done in accordance with DIN 5817 resp. 15429, by a qualified welder according to EN 287-1.

Safety factor: 4:1

Grade: 8

Excavator Hook Green Pin® GH

Blueprint



Technical data

Part code	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Weight kg
420500100380	1	72	78	25	19	28	108	31	26	0.52
420500200380	2	91	83	33	20	28	113	31	34	0.7
420500300380	3	105	105	33	26	32	129	31	34	1.15
420500400380	4	121	130	35	27	37	148	41	38	1.66
420500500380	5	138	149	43	28	45	167	41	44	2.36
420500800380	8	145	148	43	41	52	173	41	51	3.32
420501000380	10	178	197	60	46	61	227	50	66	6.44
420501500380	15	185	223	65	60	70	251	55	80	9.7