

Eye Self Locking Green Pin® UXLO

Product information



The Green Pin® Self-Locking Hook E is a grade 10 eye self-locking hook. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The eye of the hook can be connected to grade 10 chain with a connecting link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Self-Locking Hook E is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

... [Read more](#)

Material: Alloy steel, quenched and tempered

Temperature range: -40°C up to +200°C


Finish: Painted blue

Safety factor: 4:1

Grade: 10

Eye Self Locking Green Pin® UXLO

Blueprint



Technical data

Part code	WLL ton	For chain Ø mm	For chain Ø inch	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	Weight kg
402300140680	1.4	6	7/32	111	24	32	16	26	47	77	147	11	7	0.51
402300260680	2.6	8	5/16	134	29	43	23	29	57	92	176	14	7	0.91
402300400680	4	10	3/8	168	35	47	32	35	69	111	219	17	10	1.79
402300680680	6.8	13	1/2	199	46	61	37	45	87	142	264	20	13	3.36
402301030680	10.3	16	5/8	247	59	74	43	56	111	185	328	26	16	7
402301600680	16	20	5/4	283	70	90	52	61	126	205	372	28	20	9.22