Eye Sling Hook Green Pin® UCSO

Product information



The Green Pin® Sling Hook E is a grade 10 eye sling hook. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The eye of the hook can be connected to grade 10 chain with a connecting link or an omega link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Sling Hook E is available in a range to suit 6 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

... *Read more*

Material: Alloy steel, quenched and tempered
Temperature range: -40°C up to +200°C
Finish: Painted blue
Note: from 10 t without flat part

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Eye Sling Hook Green Pin® UCSO

Blueprint



Technical data

Part code	WLL ton	Inch "	For chain Ø mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
402300140660	1.4	7/32	6	86	23	27	15	19	43	73	115	10	7	0.28
402300250660	2.6	5/16	8	102	26	27	19	23	51	87	137	13	8	0.52
402300400660	4	3/8	10	121	35	28	23	29	66	106	165	16	11	1.09
402300670660	6.8	1/2	13	155	41	33	31	36	76	136	208	19	14	1.94
402301000660	10.3	5/8	16	185	48	46	34	43	92	159	252	22	17	3.51
402301600660	16	3/4	20	237	61	61	49	61	115	208	326	28	21	7.08

© November 2026 - All Rights Reserved