

Self Locking Hook SE RT Green Pin® UXLERT

Product information



The Green Pin® Self-Locking Hook SE RT is a grade 10 swivel self-locking hook with a recessed trigger. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. The trigger has been recessed into the body of the hook to prevent being snatched or damaged. This hook offers complete safety for lifting as the latch cannot be removed. The large eye is supplied with a flat part, which enables easy assembly of wire rope slings with thimbles or chain slings with omega links. These hooks are fitted with a needle roller thrust bearing. This enables smooth, easy rotation under load. The eye of the hook can also be connected to grade 10 chain with a connecting link or to a webbing with a web sling connector. The Green Pin® Self-Locking Hook SE RT is available in a range to suit 8 mm up to 20 mm grade 10 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, DGUV

[... Read more](#)

Material: Alloy steel

Temperature range: -40°C up to +200°C


Finish: Painted blue

Safety factor: 4:1

Grade: 10

Self Locking Hook SE RT Green Pin® UXLERT

Blueprint



Technical data

Part code	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
402300262060	2.6	149	41	37	43	24	28	91	232	14	8	1.38
402300402060	4	186	47	48	48	32	34	112	283	16	11	2.54
402300682060	6.8	214	60	58	63	37	44	141	337	21	14	4.54
402301032060	10.3	273	67	73	75	43	56	182	420	25	17	9.48
402301602060	16	304	87	82	90	52	62	205	478	25	21	12.4