

Self Locking Hook Green Pin® XLC

Product information



The Green Pin® Self-Locking Hook is a grade 8 clevis self-locking hook according to European standard for components for sling EN 1677-3. The self-locking hook locks automatically as soon as it is brought under tension. To release the load the user must manually unlock the hook, which prevents unintended release. This hook brings a full safety for lifting as the latch cannot be removed. The clevis design enables a direct connection to grade 8 chain. The Green Pin® Self-Locking Hook CL is available in a range to suit 5 mm up to 18/20 mm grade 8 chain.

Certification on request: 2.1, 2.2, 3.1, MPIb, DGUV

[... Read more](#)

Material: Alloy steel

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Painted white


Standard: EN 1677-3

Safety factor: 4:1

Grade: 8

Self Locking Hook Green Pin® XLC

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm
401300081090	5	0.8	93	7	32	17	24	28	75	130	8
401300111090	6	1.12	93	7	32	17	24	28	75	130	8
401300201090	7-8	2	116	9	43	24	28	32	91	161	9
401300321090	10	3.2	144	12	48	32	34	42	112	201	13
401300541090	13	5.4	169	15	63	37	44	54	141	242	16
401300821090	16	8.2	204	18	75	43	56	68	182	296	20
401301281090	18-20	12.8	234	22	90	52	62	82	205	341	24