

Sling Hook Green Pin® CSEI, Stainless Steel

Product information



The Green Pin® Stainless Steel Sling Hook SE is a grade 5 stainless steel swivel sling hook with eye. The non-corrosive nature of stainless steel makes it the perfect choice for use in industries such as foods, nuclear and sailing. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The large eye, designed with a flat enables an easy assembly on anti-rotating wire rope slings (with an omega link or with thimbles). These hooks are fitted with a stainless steel washer. The eye of the hook can also be connected to grade 5 chain with a connecting link or to a webbing with a web sling connector. The Green Pin® Stainless Steel Sling Hook SE is available in a range to suit 6 mm up to 13 mm grade 5 chain.

Certification on request: 2.1, 2.2, 3.1

... [Read more](#)

Material: AISI 316L

Temperature range: -40°C up to +200°C


Finish: Polished

Safety factor: 4:1

Grade: 5

Sling Hook Green Pin® CSEI, Stainless Steel

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
400300070120	6	0.7	100	33	32	26	15	20	72	164	11	6	0.54
400300120120	7-8	1.2	126	40	37	30	20	25	87	204	13	8	0.77
400300160120	10	1.6	158	47	48	33	24	29	106	250	16	11	1.92
400300270120	13	2.7	189	59	58	37	32	39	133	308	21	13.5	3.39