

Sling Hook Green Pin® CSOI, Stainless Steel

Product information



The Green Pin® Stainless Steel Sling Hook E is a grade 5 stainless steel eye sling hook. The non-corrosive nature of stainless steel makes it the perfect choice for use in industries such as foods, nuclear and sailing. The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The eye of the hook can be connected to grade 5 chain with a connecting link or an omega link, to a webbing with a web sling connector or to a wire rope with a thimble. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Stainless Steel Sling Hook E is available in a range to suit 6 mm up to 13 mm grade 5 chain.

Certification on request: 2.1, 2.2, 3.1

[... Read more](#)

Material: AISI 316L

Temperature range: -40°C up to +200°C


Finish: Polished

Safety factor: 4:1

Grade: 5

Sling Hook Green Pin® CSOI, Stainless Steel

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	Weight kg
400300070110	6	0.7	86	23.5	26	15	19	43	72	114	9.5	6	0.28
400300120110	7-8	1.2	103	26	30	19.5	24	51	87	139	12	8	0.57
400300160110	10	1.6	129	36	33	24	28	65	106	171	14.5	10	1.02
400300270110	13	2.7	152	41	37	31	39	77	133	209	18	12	1.97