

## DNV Master Link Assembly Green Pin® P-6820

---

### Product information



The Green Pin® DNV Master Link Assembly is perfect for offshore use. The Master Link Assembly is DNV-certified and has a large opening to accommodate larger lifting points. Moreover, the coating of the DNV Master Link Assembly ensures long-term durability, even under severe environmental conditions. The DNV Master Link Assembly is available in a range with a working load limit from 4.1 up to 100 ton.

Certification on request: 2.1, 2.2, 3.1, MTCb, MPIb, DNV 2.7-1a

... [Read more](#)

---

**Material:** Alloy steel

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C


**Standard:** DNV 2.7-1 Approved, EN 1677-4, EN 12079-2

**Safety factor:** 5:1

**Grade:** 8

## DNV Master Link Assembly Green Pin® P-6820

### Blueprint



### Technical data

Part code	WLL ton	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	Weight kg
401100410890	4.1	16	150	75	14.5	125	60	1.62
401100700890	7	22	270	140	22	162	90	5.22
401100930890	9.3	26	270	140	22	162	90	6.05
401101450890	14.5	28	270	140	22	162	90	6.73
401101900890	19	32	270	140	28	200	110	10.9
401102600890	26	36	270	140	28	200	110	12.4
401103050890	30.5	40	280	155	32	270	140	18.5
401104000890	40	45	320	175	36	270	140	25.1
401105100890	51	50	350	195	45	320	175	40.9
401107500890	75	65	410	220	50	350	195	66.1
401110000890	100	75	450	250	65	410	220	115