

Master Link Assembly Green Pin® MTS Grade 8

Product information



The Green Pin® Master Link Assembly EN1677-4 is a grade 8 master link assembly according to European standard for components for sling EN 1677-4. This welded master link assembly is designed for 3 or 4 leg sling. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Master Link Assembly EN1677-4 is available in a range with a working load limit from 2.5 t. up to 100 t.

Certification on request: 2.1, 2.2, 3.1, MTCb, MPIa

[... Read more](#)

Material: Alloy steel

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Painted white

Standard: EN 1677-4


Note: From 60 t without flat part

Safety factor: 4:1

Grade: 8

Master Link Assembly Green Pin® MTS Grade 8

Blueprint



Technical data

Part code	WLL ton	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	Weight kg
401100250820	2.5	16	120	70	13	115	60	7	1.2
401100350820	3.5	18	135	75	16	120	70	7	3.1
401100650820	6.5	22	170	90	18	135	75	9	3.3
401100850820	8.5	25	190	103	20	150	82	11	4.5
401101000820	10	28	209	120	20	150	82	11	5.4
401101300820	13	30	235	125	22	170	90	14	7.2
401101700820	17	36	270	145	25	190	103	14	11.2
401102080820	20.8	38	250	150	28	209	120	17	13.3
401103000820	30	45	300	200	36	270	145	22	25.3
401104000820	40	50	380	200	38	250	150	22	32.2
401105000820	50	55	360	200	38	250	150	22	35.2
401106000820	60	60	430	220	45	300	200	45	54.2
401108000820	80	70	500	250	55	360	200	55	86