



Master Link Green Pin® MS

Product information

The Green Pin® Master Link EN1677-4 is a single grade 8 master link according to European standard for components for sling EN 1677-4. This welded master single link is designed for a 1 or 2 leg sling. The flat on the eye enables the assembly with an omega link or on a thimble. The Green Pin® Master Link EN1677-4 is available in a range with a working load limit from 1.6 t. up to 125 t.

Certification on request: 2.1, 2.2, 3.1, MTCb, MPIa

Material: Alloy steel

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Painted white

Standard: EN 1677-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter	WLL ton	a mm	b mm	c mm	d mm	Weight kg
401100160490	13	1.6	13	115	60	7	0.4
401100320490	16	3.2	16	120	70	7	0.6
401100450490	18	4.5	18	135	75	9	0.84
401100620490	20	6.2	20	150	90	11	1.1
401100820490	22	8.2	22	170	90	14	1.6
401101060490	25	10.6	25	190	103	14	2.3
401101280490	28	12.8	28	209	120	17	3.1
401101550490	30	15.5	30	235	125	17	4
401102000490	36	20	36	270	145	22	6.6
401102500490	38	25	38	250	150	22	7.1
401103700490	45	37	45	300	200	22	12.1
401105000490	50	50	50	380	200	50	18
401106300490	55	63	55	360	200	55	21
401110000490	70	100	70	500	250	70	44
401112500490	80	125	80	503	280	80	60.7

Blueprint

