Clevis Master Set Pewag VMXKW 4

Product information



VMXKW Clevis master sets are designed for the assembly of 4-leg chain slings with welded-in XKW shortening element.
Master sets with welded-in XKW shortening element.

... *Read more*


Material: High duty grade 10.
Marking: According to standard, CE-mark
Temperature range: -40ºC up to +380°C.
Finish: Orange powder coated.
Standard: EN 818-4

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Clevis Master Set Pewag VMXKW 4

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	EWL mm	WLL 45- 60° ton	Use for hook DIN 15401 Nr	Double hook DIN 15402 no.	d mm	e mm	t mm	w mm mm	Weight kg
402100300680	VMXKW 4-5/6	6	3	273	2,12	6	8	19	298	160	75	2.63
402100400680	VMXKW 4-7	7	4	352	2,8	10	12	23	362	170	90	4.84
402100530680	VMXKW 4-8	8	5.3	352	3,75	10	12	23	362	170	90	4.93
402100800680	VMXKW 4-10	10	8	424	6	10	12	27	434	190	100	9.01
402101400680	VMXKW 4-13	13	14	518	10	12	16	33	548	230	110	17.9
402102120680	VMXKW 4-16	16	21.2	633	15	20	25	38	649	275	140	30.52

© November 2026 - All Rights Reserved