

Coupling Ring Pewag KRW

Product information



pewag

KRW Coupling rings are designed for the assembling of chain slings. They serve as a linking element for pewag winner lifting chains of the same nominal size when building chain slings.

Connecting part for clevis master links, and as a chain-connecting component in specific designs.

[... Read more](#)

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.


Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Coupling Ring Pewag KRW

Blueprint



Technical data

Part code	Code	WLL ton	a mm	b mm	d mm	e mm	f mm	s mm	Weight kg
402200140330	KRW 5/6	1.4	18	38	7	31	8	7	0.08
402200190330	KRW 7	1.9	24	54	9	43	11	10	0.2
402200250330	KRW 8	2.5	24	54	10	43	11	10	0.2
402200400330	KRW 10	4	28	63	12.5	51	14	12	0.36
402200670330	KRW 13	6.7	33	76	16	63	17	15	0.7
402201000330	KRW 16	10	40	88	20	74	20	18	1.21
402201600330	KRW 19/20	16	50	114	24	94	24	23	2.38
402201900330	KRW 22	19	50	122	27	102	27	25	3.21