

Master Link Assembly Pewag VMW Enlarged

Product information



VMW Enlarged master link assemblies are designed for pewag connex and welded system. For assembling 3- and 4-leg chains with connex links CW. For assembling of welded chain slings with BW by pewag. Similar to VW 4-leg set, but also suitable for larger crane hooks and special hooks.

[... Read more](#)

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.


Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Master Link Assembly Pewag VMW Enlarged

Blueprint



Technical data

Part code	Code	WLL ton	EWL	Consisting of	Use for hook DIN 15401 Nr	Double hook DIN 15402 no.	e mm	t mm	w mm	mm	Weight kg
402100420320	VMW 6	4.2	214	MW 18 + 2 BW 13	6	8	214	160	95		1.43
402100660320	VMW 7/8	6.6	240	MW 22 + 2 BW 16	10	12	240	170	105		2.46
402101010320	VMW 10	10.1	275	MW 26 + 2 BW 20	10	12	275	190	110		4.01
402101570320	VMW 13	15.7	345	MW 32 + 2 BW 22	12	16	345	230	130		7.1
402102120320	VMW 16	21.2	415	MW 36 + 2 BW 26	20	25	415	275	150		11.3
402103410320	VMW 19/20	34.1	500	MW 56 + 2 BW 32	50	63	500	350	250		28.3
402104000320	VMW 22	40	520	MW 56 + 2 BW 36	50	63	520	350	250		30.22