

Swivel Safety Hook Pewag WLHBW

Product information



The swivel safety hook closes and locks automatically and comes with an axial bearing, ensuring that it may be rotated when under load, but not opened. It is suitable for Connex systems and also offers additional connecting options thanks to its large swivel casing. Its jaw opening is larger than the HSW eye hook, making it more flexible in terms of potential use.

[... Read more](#)

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +120°C.

Finish: Orange powder coated.

Standard: EN 1677-3


Note: This product is suitable for straight pull only, and the tip of the hook and the safety catch must not be placed under load. The hook should not be used in the welded system.

Safety factor: 4:1

Grade: 10

Swivel Safety Hook Pewag WLHBW

Blueprint



Technical data

Part code	Code	WLL ton	EWL mm	a mm	d2 mm	e mm	g mm	h mm	w mm mm	w2 mm	s max. mm mm	Weight kg
420500140610	WLHBW 5/6	1.4	161	17	12	161	28	20	35	36	1	1.2
420500250610	WLHBW 7/8	2.5	181	20	12	181	34	26	35	35	1	1.55
420500400610	WLHBW 10	4	218	29	16	218	45	30	42	41	1	2.14
420500670610	WLHBW 13	6.7	269	35	20	269	52	40	49	47	1.5	4.43
420501000610	WLHBW 16	10	319	41	24	319	60	50	60	60	2	7.35