



GN SO1 Closed Spelter Socket

Product information

We deliver a high quality GN SO1 Closed Spelter Socket in cast steel

Material: Cast steel.

Finish: Painted/galvanized.

Safety factor: 5:1.

Part code	Rope Ø range mm	MBL	Finish	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
122100700082	6-7	8	Galvanized	51	46	11	8	20	37	13	0.3
122101000082	8-10	12	Galvanized	51	52	14	11	24	43	16	0.4
122101300082	11-13	20	Galvanized	64	59	18	14	29	51	22	0.8
122101600082	14-16	30	Galvanized	77	65	20	18	35	67	25	1.4
122101900082	18-19	40	Galvanized	90	75	26	21	42	75	31	2.1
122102200080	20-22	60	-	101	90	33	24	47	92	38	4
122102600080	23-26	75	-	114	103	36	28	57	104	44	7

122103000080	27-30	100	-	127	116	39	32	63	114	51	8
122103600080	31-36	125	-	139	130	43	38	70	127	57	11
122103900080	37-39	150	-	152	155	51	41	79	136	63	13
122104200080	40-42	180	-	165	171	54	44	82	146	70	17
122104800080	43-48	230	-	190	198	55	51	89	171	76	24
122105400080	49-54	280	-	216	224	62	57	96	193	82	37
122106000080	55-60	375	-	228	247	73	63	108	216	92	50
122106800080	61-68	425	-	248	270	79	73	140	241	102	65
122107500080	69-75	500	-	279	286	76	79	159	273	124	93
122108000080	76-80	600	-	305	298	83	86	171	292	133	110
122108600080	81-86	700	-	330	311	102	92	1,847	311	146	142
122109300080	87-93	750	-	356	330	102	99	197	330	159	170
122110200080	94-102	950	-	381	356	108	108	216	362	178	225
122111500080	108-115	1,200	-	450	425	120	125	235	405	190	340
122113000080	122-130	1,400	-	500	475	120	138	260	515	205	555
122115500080	140-155	2,000	-	580	550	150	160	300	550	225	850
122116700080	158-167	2,490	-	675	600	175	175	325	600	300	1,050