



GN SO2 Open Spelter Socket

Product information

We deliver a quality painted and galvanized GN SO2 Open Spelter Socket in cast steel.

Material: Cast steel.

Finish: Painted/galvanized.

Safety factor: 5:1.

Part code	Rope Ø range mm	MBL	A,	B,	C,	D,	D1 mm	J,	K,	Weight kg
122100700090	6-7	3	52	40	34	8	18	17	8	0.4
122101000090	8-10	6	58	45	40	11	21	20	11	0.6
122101300090	11-13	12	64	51	49	14	26	25	12	1.3
122101600090	14-16	24	76	64	62	18	30	32	14	2
122101900090	18-19	32	89	76	80	21	35	38	16	3
122102200090	20-22	45	101	89	90	24	41	44	19	5
122102600090	23-26	70	114	101	120	28	51	51	22	8

122103000090	27-30	100	127	114	130	32	57	57	25	12
122103600090	31-36	125	139	127	144	38	63	63	28	17
122103900090	37-39	150	152	162	160	41	70	76	30	24
122104200090	40-42	200	165	165	176	44	76	76	33	28
122104800090	43-48	260	190	178	200	51	89	89	39	41
122105400090	49-54	280	216	228	216	57	95	101	46	61
122106000090	55-60	360	228	250	236	63	108	113	53	90
122106800090	61-68	450	248	273	264	73	121	127	60	122
122107500090	69-75	480	279	279	276	79	127	133	73	157
122108000090	76-80	520	305	286	284	86	133	146	76	195
122108600090	81-86	600	330	298	296	92	140	159	79	221
122109300090	87-93	700	356	318	340	99	152	171	83	281
122110200090	94-102	875	381	343	362	108	178	191	89	397
122111500090	108-115	1,100	460	480	440	125	190	208	101	570
122113000090	122-130	1,250	500	500	560	138	250	210	120	980
122115500090	140-155	1,400	580	500	600	160	275	230	140	1,040
122116700090	158-167	1,600	675	600	650	175	290	310	175	1,175