



## Thimble Heavy Duty Stub-end K2-B GN

### Product information

Suitable for wire rope.

Standard certification : Certificate of Conformity

**Material:** Mild steel.

**Temperature range:** -20°C up to +200°C

**Finish:** Galvanized.

| Part code    | Rope Ø range mm | A mm  | B mm | C mm | D mm | E mm | F mm | G mm | Weight kg/100pc |
|--------------|-----------------|-------|------|------|------|------|------|------|-----------------|
| 123101500330 | 14-15           | 101.6 | 75   | 50   | 50   | 17   | 22   | 6    | 40              |
| 123101700330 | 16-17           | 114.3 | 85   | 50   | 53   | 19   | 25   | 6    | 50              |
| 123101900330 | 18-19           | 127   | 100  | 60   | 60   | 21   | 29   | 8    | 80              |
| 123102100330 | 20-21           | 139.7 | 110  | 60   | 65   | 23   | 33   | 8    | 90              |
| 123102300330 | 22-23           | 152.4 | 115  | 70   | 70   | 25   | 34   | 8    | 100             |
| 123102700330 | 24-27           | 177.8 | 135  | 75   | 80   | 30   | 38   | 10   | 170             |
| 123103000330 | 28-30           | 203.2 | 155  | 80   | 100  | 33   | 44   | 10   | 250             |
| 123103400330 | 31-34           | 228.6 | 175  | 110  | 115  | 38   | 49   | 10   | 400             |
| 123103700330 | 35-37           | 254   | 190  | 120  | 120  | 41   | 52   | 15   | 450             |
| 123104200330 | 38-42           | 279.4 | 210  | 120  | 130  | 46   | 60   | 15   | 700             |
| 123104700330 | 43-47           | 304.8 | 245  | 140  | 145  | 52   | 65   | 15   | 830             |
| 123105400330 | 48-54           | 355.6 | 260  | 155  | 155  | 60   | 72   | 20   | 1,250           |
| 123106300330 | 55-63           | 431.8 | 310  | 200  | 190  | 70   | 84   | 20   | 1,800           |
| 123107300330 | 64-73           | 482.6 | 350  | 235  | 230  | 81   | 119  | 20   | 3,050           |
| 123108300330 | 74-83           | 558.8 | 395  | 240  | 255  | 92   | 130  | 20   | 4,050           |
| 123109500330 | 84-95           | 609.6 | 430  | 275  | 280  | 105  | 145  | 25   | 4,950           |
| 123110900330 | 96-109          | 660.4 | 450  | 295  | 285  | 120  | 155  | 30   | 5,400           |

Blueprint

